

# USB 1.1 Rover® 1850

## 1-Port USB 1.1 85m\* Cat 5e Extender System

The USB 1.1 Rover 1850 extends USB 1.1 connections beyond the desktop up to 85\* meters.





15.2cm (6")

### **Features**

The Rover 1850 uses technology ideal for extending USB peripherals including: keyboards, mice, interactive white boards, and game controllers and does not require external power adapters. Key features include:

- Remote extender supplies up to 400mA\*\* to USB devices
- Supports both full-speed (12 Mbps) and low-speed (1.5 Mbps) throughputs
- Robust ESD and EFT immunity for industrial environments
- 3-year warranty

Includes the ExtremeUSB® suite of features:

- True plug and play; no software drivers required
- Supports all major operating systems: Windows<sup>®</sup>, Mac OS X<sup>®</sup>, and Linux<sup>®</sup>
- Reliable operation with all USB 2.0 and 1.1 devices, including hubs
- Patented USB extension technology

### **Applications**

- Interactive white board
- Sensor/data acquisition
- Keyboard and mouse
- Industrial control

Specifications subject to change without notification. Icron Technologies Corp. #90-00874-A04



- \* Up to 40m for all USB devices; 85m is achievable for most low powered HID USB devices.
- \*\* 400mA when LEX is supplied with 700mA

# Use none 1850

Specifications subject to change without notification.
©2013
Icron Technologies Corp.
#90-00874-A04



Full-Speed and Low-Speed: Up to 40m (131 ft)
Low-Speed: Up to 85m (279 ft)\*

LEX (LOCAL EXTENDER)

USB Connector: 1 x USB Type A Plug

Pig Tail Length: 45.7cm (18")

Link Connector: 1 x RJ45

Dimensions: 85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")

Enclosure Material: Black ABS

REX (REMOTE EXTENDER)

USB Connector: 1 x USB Type A Receptacle

Pig Tail Length: 15.2cm (6")
Link Connector: 1 x RJ45

Maximum Current Available: 400mA when LEX is supplied with 700mA

Dimensions: 85mm x 40mm x 22mm (3.34" x 1.57" x 0.87")

Enclosure Material: Black ABS

**ENVIRONMENTAL** 

Operating Temperature: 0°C to 50°C (32°F to 122°F)

**COMPLIANCE** 

Emissions: FCC (Class A), CE (Class A)

Immunity: CE Criteria A

Environmental: RoHS2 (CE)

Safety: CPSIA, Flammability V-1

**SUPPORT** 

Warranty: 3 years

\* device and host dependant

### **Ordering Information**

The USB 1.1 Rover® 1850 system includes a LEX, REX, Quick Start Guide and three year warranty. For more information, email sales@icronshop.com or call +44 1273 731 555.

PART # NAME DESCRIPTION

00-00301 USB 1.1 Rover® 1850 1-Port 85m Cat 5e bus-powered USB Extender System