

# Power Adapters

## AC power adapters



### Features and Benefits

- 100 to 240 VAC power input
- -40 to 75°C operating temperature range (-T models)

### Certifications



## Introduction

The power adapters in Moxa's Power Adapter Series provide a reliable power source for many Moxa products.

## Specifications

### Input Power Parameters

|               |                              |
|---------------|------------------------------|
| Voltage Range | 100 to 240 VAC (50 to 60 Hz) |
|---------------|------------------------------|

### Power Parameters

|                     |   |
|---------------------|---|
| Input Plug Type     | PWR-AU Models: Australia plug type<br>PWR-CN Models: China plug type<br>PWR-EU Models: Europe plug type<br>PWR-UK Models: United Kingdom plug type<br>PWR-USJP Models: United States/Japan plug type<br>PWR-KR Models: Korea plug type  |
| Output Power Rating | PWR-12050 Models: 0.5 A @ 12 VDC<br>PWR-12150 Models: 1.5 A @ 12 VDC<br>PWR-12200-DT-S1: 2 A @ 12 VDC<br>PWR-12300 Models: 3 A @ 12 VDC   |
| Output Plug Type    | PWR-12050-S1 Models: S-Type 5.5/2.1/7.5<br>PWR-12050-S2 Models: S-Type 5.5/2.1/9.5<br>PWR-12150-S2 Models: S-Type 5.5/2.1/9.5<br>PWR-12200-DT-S1: S-Type 5.5/2.1/7.5<br>PWR-12300 Models: S-Type 5.5/2.1/7.5<br>PWR-12150-SA-T Models: L-Type 5.5/2.1/7.5<br>Outer Diameter: 5.5 ± 0.1 mm (0.22 ± 0.004 in)<br>Inner Diameter: 2.1 ± 0.1 mm (0.08 ± 0.004 in) |

## Physical Characteristics

|  |  |
|--|--|
| <p><b>Dimensions</b></p>                   | <p>PWR-12050-AU-S1: 67.9 x 33.5 x 39.4 mm (2.67 x 1.32 x 1.55 in)<br/> PWR-12050-CN-S1: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in)<br/> PWR-12050-EU-S1: 68.0 x 33.0 x 55.0 mm (2.68 x 1.30 x 2.17 in)<br/> PWR-12050-KR-S1: 67.7 x 33.0 x 55.1 mm (2.67 x 1.30 x 2.17 in)<br/> PWR-12050-UK-S1: 67.8 x 50.3 x 43.0 mm (2.67 x 1.98 x 1.69 in)<br/> PWR-12050-USJP-S1: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in)<br/> PWR-12050-AU-S2: 67.9 x 39.4 x 42.5 mm (2.67 x 1.55 x 1.67 in)<br/> PWR-12050-CN-S2: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in)<br/> PWR-12050-EU-S2: 68.0 x 33.0 x 55.0 mm (2.68 x 1.30 x 2.17 in)<br/> PWR-12050-KR-S2: 67.7 x 33.0 x 55.1 mm (2.67 x 1.30 x 2.17 in)<br/> PWR-12050-UK-S2: 67.9 x 50.3 x 43.0 mm (2.67 x 1.98 x 1.69 in)<br/> PWR-12050-USJP-S2: 67.8 x 33.0 x 39.0 mm (2.67 x 1.30 x 1.54 in)<br/> PWR-12150-WPAU-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPCN-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPEU-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12300-WPUK-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPUSJP-S2: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPAU-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPCN-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPEU-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPKR-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPUK-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12150-WPUSJP-S4: 80.5 x 39.1 x 56.4 mm (3.17 x 1.54 x 2.22 in)<br/> PWR-12300-WPAU-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in)<br/> PWR-12300-WPCN-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in)<br/> PWR-12300-WPEU-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in)<br/> PWR-12300-WPUK-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in)<br/> PWR-12300-WPUSJP-S2: 93.0 x 50.0 x 39.6 mm (3.66 x 1.97 x 1.56 in)<br/> PWR-12150-AU-SA-T: 41 x 73.9 x 89.5 mm (1.61 x 2.91 x 3.52 in)<br/> PWR-12150-CN-SA-T: 32 x 60 x 88 mm (1.26 x 2.36 x 3.46 in)<br/> PWR-12150-EU-SA-T: 32 x 85.3 x 88 mm (1.26 x 3.36 x 3.46 in)<br/> PWR-12150-UK-SA-T: 50 x 91 x 82.5 mm (1.97 x 3.58 x 3.25 in)<br/> PWR-12150-USJP-SA-T: 32 x 70.3 x 88 mm (1.26 x 2.77 x 3.46 in)<br/> PWR-12200-DT-S1: 110.8 x 51.8 x 32 mm (4.36 x 2.04 x 1.26 in)</p> |
| <p><b>Weight</b></p>                       | <p>PWR-12050 Models: 71~87 g ( 0.16 ~ 0.19 lb )<br/> PWR-12150 Models: 200 g ( 0.44 lb )<br/> PWR-12150-S2 Models: 115 g ( 0.25 lb )<br/> PWR-12300-S1 Models: 163 g ( 0.36 lb )<br/> PWR-DT Models: 200 g ( 0.44 lb )</p>   |
| <p><b>Cord Length</b></p>                  | <p>PWR-12050 Models: 1500±100 mm (59.06±3.94 in)<br/> PWR-12150 Models: 1500±100 mm (59.06±3.94 in)<br/> PWR-12300 Models: 1500±100 mm (59.06±3.94 in)<br/> PWR-12200-DT-S1: 1800±200 mm (70.87±7.87 in)</p>   |
| <p><b>Environmental Limits</b></p>         |  |
| <p><b>Operating Temperature</b></p>        | <p>Standard Models: 0 to 40°C (32 to 104°F)<br/> Wide Temp. Models: -40 to 75°C (-40 to 167°F)</p>   |
| <p><b>Storage Temperature</b></p>          | <p>Standard Models: -20 to 70°C (-4 to 158°F)<br/> Wide Temp. Models: -40 to 75°C (-40 to 167°F)</p>   |
| <p><b>Standards and Certifications</b></p> |  |
| <p><b>Safety</b></p>                       | <p>PWR-12050-AU Models: RCM<br/> PWR-12050-CN Models: CCC<br/> PWR-12050-EU Models: CE/GS<br/> PWR-12050-KR Models: KCC<br/> PWR-12050-UK Models: CE<br/> PWR-12050-USJP Models: FCC/UL/PSE<br/> PWR-12150 Models: CE/FCC/UL/RCM/PSE/CCC/GS/KCC<br/> PWR-12300 Models: CE/FCC/UL/RCM/PSE/CCC/GS<br/> PWR-12200-DT-S1: Efficiency Level 5: CE/FCC/UL/RCM/PSE/CCC; Efficiency Level 6: CE/FCC/UL/PSE<br/> PWR-12150-AU-SA-T: RCM<br/> PWR-12150-CN-SA-T: CCC<br/> PWR-12150-EU-SA-T: TUV/CE/GS<br/> PWR-12150-UK-SA-T: CE<br/> PWR-12150-USJP-SA-T: FCC/UL/PSE</p>   |

## Warranty

|                 |  |
|-----------------|--|
| Warranty Period | 1 years  |
| Details         | See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a> |

## Ordering Information

| Model Name          | Barrel-plug Type | Input-plug Type | Output Rating  | Operating Temperature |
|---------------------|------------------|-----------------|----------------|-----------------------|
| PWR-12050-AU-S1     | Locking          | AU              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-CN-S1     | Locking          | CN              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-EU-S1     | Locking          | EU              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-KR-S1     | Locking          | KR              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-UK-S1     | Locking          | UK              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-USJP-S1   | Locking          | US/JP           | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-AU-S2     | Non-locking      | AU              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-CN-S2     | Non-locking      | CN              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-EU-S2     | Non-locking      | EU              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-KR-S2     | Non-locking      | KR              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-UK-S2     | Non-locking      | UK              | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12050-USJP-S2   | Non-locking      | US/JP           | 0.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPAU-S2   | Non-locking      | AU              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPCN-S2   | Non-locking      | CN              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPEU-S2   | Non-locking      | EU              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPUK-S2   | Non-locking      | UK              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPUSJP-S2 | Non-locking      | US/JP           | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPAU-S4   | Locking          | AU              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPCN-S4   | Locking          | CN              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPEU-S4   | Locking          | EU              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPKR-S4   | Locking          | KR              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPUK-S4   | Locking          | UK              | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12150-WPUSJP-S4 | Locking          | US/JP           | 1.5 A @ 12 VDC | 0 to 40°C             |
| PWR-12300-WPAU-S2   | Locking          | AU              | 3 A @ 12 VDC   | 0 to 40°C             |
| PWR-12300-WPCN-S2   | Locking          | CN              | 3 A @ 12 VDC   | 0 to 40°C             |
| PWR-12300-WPEU-S2   | Locking          | EU              | 3 A @ 12 VDC   | 0 to 40°C             |
| PWR-12300-WPUK-S2   | Locking          | UK              | 3 A @ 12 VDC   | 0 to 40°C             |
| PWR-12300-WPUSJP-S2 | Locking          | US/JP           | 3 A @ 12 VDC   | 0 to 40°C             |
| PWR-12150-AU-SA-T   | Locking          | AU              | 1.5 A @ 12 VDC | -40 to 75°C           |
| PWR-12150-CN-SA-T   | Locking          | CN              | 1.5 A @ 12 VDC | -40 to 75°C           |
| PWR-12150-EU-SA-T   | Locking          | EU              | 1.5 A @ 12 VDC | -40 to 75°C           |
| PWR-12150-UK-SA-T   | Locking          | UK              | 1.5 A @ 12 VDC | -40 to 75°C           |
| PWR-12150-USJP-SA-T | Locking          | US/JP           | 1.5 A @ 12 VDC | -40 to 75°C           |
| PWR-12200-DT-S1     | Locking          | Desktop         | 2 A @ 12 VDC   | 0 to 40°C             |

© Moxa Inc. All rights reserved. Updated Aug 06, 2021.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.